

## Toshiba Air Conditioning Data Sheet

MMU-UP0181SH-E  
VRF 1 WAY CASSETTE



Model Reference		MMU-UP0181SH-E	
<b>Capacity Code</b>		HP	2.0
Nominal	Cooling Capacity	kW	5.6
	Heating Capacity	kW	6.3
UK	Cooling Total/Sensible	kW	5.1/3.7
	Heating	kW	4.3
Electrical	Power Input	kW	0.046
	Run Current	Amps	0.37
	Start Current	Amps	0.54
Air Flow	High - Medium - Low	l/s	217 - 200 - 183
	High - Medium - Low	m <sup>3</sup> /h	780 - 720 - 660
Sound	Pressure High - Medium - Low	dB(A)	38 - 36 - 34
	Power High - Medium - Low	dB(A)	53 - 51 - 49
Unit	Height x Width x Depth	mm	200 x 1000 x 710
	Weight	kg	21
Panel	Height x Width x Depth	mm	20 x 1230 x 800
	Weight RBC-US21PGE	kg	5.5
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

# TOSHIBA

- Low noise level that can operate down to 25dB(A)
- Ideal for false ceiling applications
- Water condensate drain pump lifts condensate water up to 350mm.

MMU-UP0151SH-E, MMU-UP0181SH-E

