

Toshiba Air Conditioning Data Sheet

MMF-UP0361H-E
VRF FLOOR MOUNTED CABINET



Model Reference		MMF-UP0361H-E	
Capacity Code		HP	4.0
Nominal	Cooling Capacity	kW	11.2
	Heating Capacity	kW	12.5
UK	Cooling Total/Sensible	kW	10.2/7.6
	Heating	kW	8.5
Electrical	Power Input	kW	0.135
	Run Current	Amps	0.90
	Start Current	Amps	1.26
Air Flow	High - Medium - Low	l/s	533 - 450 - 383
	High - Medium - Low	m ³ /h	1920 - 1620 - 1380
Sound	Pressure High - Medium - Low	dB(A)	51 - 46 - 41
	Power High - Medium - Low	dB(A)	66 - 61 - 56
Unit	Height x Width x Depth	mm	1750 x 600 x 390
	Weight	kg	62
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	20 male screw
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

TOSHIBA

- High air flows: From 180 l/s to 600 l/s (660 m³/h to 2160 m³/h)
- Wide air distribution angle: up to 150°
- Cooling capacities from 4.5 kW to 16 kW
- Heating capacities from 5 kW to 18 kW
- Very small footprint: 0.128 m² up to 8 kW and 0.243 m² up to 16 kW

External views

(Unit: mm)

