


VRF 2-WAY CASSETTE: MMU - UPO481WH-E

- Compact dimensions (height 345mm).
- Minimal weight (36 kg) for units up to 18kw.
- Enhanced indoor air quality with standard long-life filters.
- Unique air flow control, provides a balanced flow of air in two opposite directions.
- The elegant white decorative panel allows the unit to be installed seamlessly into any room.



Hi - Res Image 



Performance Data

Capacity Code		HP	5.0
Nominal	Cooling Capacity	kW	14.0
	Heating Capacity	kW	16.0
UK	Cooling Total/Sensible	kW	12.7/8.5
	Heating	kW	10.9
Electrical	Power Input	kW	0.091
	Run Current	Amps	0.59
	Start Current	Amps	0.89

Indoor Data

Airflow	High - Medium - Low	l/s	500 - 412 - 342
	High - Medium - Low	m3/h	1800 - 1482 - 1230
Sound	Pressure High - Medium - Low	dB(A)	43 - 40 - 37
	Power High - Medium - Low	dB(A)	58 - 55 - 52
Unit	Height x Width x Depth	mm	345 x 1600 x 570
	Weight	kg	36
Panel	Type	RBC-	UW1403PG(W)-E
	Height x Width x Depth	mm	20 x 1835 x 680
	Weight	kg	14
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

Accessories

RBC-AMTU31-E	Standard Remote Controller - Full control including service functions
RBC-ASCU11-E	Compact Remote Controller - Includes timer off, back light display, multilingual
RBC-AWSU52-E	Premium Controller - Includes timer and back light display, multilingual (inc. Bluetooth)
RBC-MTSC1	Mini Touch Screen Controller - with configurable icons for indoor units
RBC-MTSC2	Mini Touch Screen Controller - with Schedule Timer, configurable icons for indoor units
TCB-FF151US-E	Auxiliary fresh air flange - For Fresh air intake by using the knock out hole of indoor unit
TBC-LF**3UW-E	Super Long Life Filter - Dust collecting effect 50% (Weight method) - Use with TBC-FC**3UW-E
TBC-FC**3UW-E	Filter chamber - Chamber for Super long life filter - Use with TBC-LF**3UW-E

*All [Accessories](#) / [Controls](#)

Compatible R410a outdoor condensers:

[Mini SMMS-e](#), [SMMS-u](#), [SHRM-e](#)

Compatible R32 outdoor condensers:

[Mini SMMS](#), [SHRM-a](#)

Related items:

- [Full specification](#)
- [BIM files](#)
- [CAD files](#)
- [Airflow/ fan curve](#)
- [Dimensional drawing](#)
- [Wiring diagram](#)
- [Noise curve data](#)
- [Installation manual](#)

