

## VRF 4-WAY COMPACT CASSETTE: MMU - UP0121MH-E

- 5-step flow with individual louvre swing control.
- Fit within the T-bar of grid ceiling: 620mm X 620mm.
- Lightweight unit, for easy and quick installation with built in high lift drain pump.
- At only 256mm height, this compact chassis is perfectly suited to confined spaces.
- Smart flat panel design with clean lines that will complement any decorative style.



Hi - Res Image



### Performance Data

Capacity Code		HP	1.3
Nominal	Cooling Capacity	kW	3.6
	Heating Capacity	kW	4.0
UK	Cooling Total/Sensible	kW	3.3/2.5
	Heating	kW	2.2
Electrical	Power Input	kW	0.027
	Run Current	Amps	0.25
	Start Current	Amps	0.44

### Indoor Data

Airflow	High - Medium - Low	l/s	165 - 140 - 112
	High - Medium - Low	m <sup>3</sup> /h	594 - 504 - 402
Sound	Pressure High - Medium - Low	dB(A)	38 - 34 - 30
	Power High - Medium - Low	dB(A)	53 - 49 - 45
Unit	Height x Width x Depth	mm	256 x 575 x 575
	Weight	kg	15
Panel	Height x Width x Depth	mm	12 x 620 x 620
	Weight RBC-UM21PG(W)-E	kg	2.5
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4
	Drain Pipe Connection ID	mm	VP20
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-3

### Accessories

<a href="#">RBC-AMTU31-E</a>	Standard Remote Controller - Full control including service functions
<a href="#">RBC-ASCU11-E</a>	Compact Remote Controller - Includes timer off, back light display, multilingual
<a href="#">RBC-AWSU52-E</a>	Premium Controller - Includes timer and back light display, multilingual (inc. Bluetooth)
<a href="#">RBC-MTSC1</a>	Mini Touch Screen Controller - with configurable icons for indoor units
<a href="#">RBC-MTSC2</a>	Mini Touch Screen Controller - with Schedule Timer, configurable icons for indoor units
<a href="#">TCB-SIR41UM-E</a>	Occupancy sensor - Cannot be used with wireless remote control kit
<a href="#">RBC-AXU31UM-E</a>	Wireless Remote Control kit - Cannot be used with Occupancy sensor
<a href="#">TCB-FF101URE2</a>	Auxiliary fresh air flange - For easy fresh air intake by using knock out hole of indoor

\*All [Accessories / Controls](#)

Compatible R410a outdoor condensers:

[Mini SMMS-e](#), [SMMS-u](#), [SHRM-e](#)

Compatible R32 outdoor condensers:

[Mini SMMS](#), [SHRM-a](#)

Related items:

- [Full specification](#)
- [BIM files](#)
- [Airflow/ fan curve](#)
- [Dimensional drawing](#)
- [Wiring diagram](#)
- [Noise curve data](#)
- [Installation manual](#)

