

VRF 4-WAY STANDARD CASSETTE: MMU - UPO241HP-E

- Possible to set three different swing modes.
- Optimal air diffusion up to 4.6m ceiling height.
- Lightweight unit, for easy and quick installation.
- Compact chassis with only 256mm height (up to size 30).
- Self-cleaning function and Ag-ion tip for anti-mould in drain cap.



Hi - Res Image 

Performance Data

Capacity Code		HP	2.5
Nominal	Cooling Capacity	kW	7.1
	Heating Capacity	kW	8.0
UK	Cooling Total/Sensible	kW	6.4/4.6
	Heating	kW	5.4
Electrical	Power Input	kW	0.036
	Run Current	Amps	0.38
	Start Current	Amps	0.42

Indoor Data

Airflow	High - Medium - Low	l/s	358 - 255 - 222
	High - Medium - Low	m3/h	1290 - 920 - 800
Sound	Pressure High - Medium - Low	dB(A)	35 - 31 - 28
	Power High - Medium - Low	dB(A)	50 - 46 - 43
Unit	Height x Width x Depth	mm	256 x 840 x 840
	Weight	kg	20
Panel	Height x Width x Depth	mm	30 x 950 x 950
	Weight RBC-U32PGP-E	kg	4
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

Accessories

RBC-AMTU31-E	Standard Remote Controller - Full control including service functions
RBC-ASCU11-E	Compact Remote Controller - Includes timer off, back light display, multilingual
RBC-AWSU52-E	Premium Controller - Includes timer and back light display, multilingual (inc. Bluetooth)
RBC-MTSC1	Mini Touch Screen Controller - with configurable icons for indoor units
RBC-MTSC2	Mini Touch Screen Controller - with Schedule Timer, configurable icons for indoor units
TCB-GFC1603U-E	Fresh Air Chamber - Fresh Air chamber for use with TCB-GB1602UE
TCB-BC1602UE	Air discharge direction kit - Air Discharge kit - With 6-direction patterns
TCB-FF101URE2	Auxiliary fresh air flange - For easy fresh air intake by using knock out hole of indoor.

*All [Accessories](#) / [Controls](#)

Compatible R410a outdoor condensers:

[Mini SMMS-e](#), [SMMS-u](#), [SHRM-e](#)

Compatible R32 outdoor condensers:

[Mini SMMS](#), [SHRM-a](#)

Related items:

- [Full specification](#)
- [BIM files](#)
- [Airflow/ fan curve](#)
- [Dimensional drawing](#)
- [Wiring diagram](#)
- [Noise curve data](#)
- [Installation manual](#)

