


## VRF 4-WAY STANDARD CASSETTE: MMU - UP0561HP-E

- Possible to set three different swing modes.
- Optimal air diffusion up to 4.6m ceiling height.
- Lightweight unit, for easy and quick installation.
- Compact chassis with only 319mm height (up to size 56).
- Self-cleaning function and Ag-ion tip for anti-mould in drain cap.



Hi - Res Image 



### Performance Data

Capacity Code		HP	6.0
Nominal	Cooling Capacity	kW	16.0
	Heating Capacity	kW	18.0
UK	Cooling Total/Sensible	kW	14.5/10.4
	Heating	kW	12.2
Electrical	Power Input	kW	0.112
	Run Current	Amps	0.88
	Start Current	Amps	1.26

### Indoor Data

Airflow	High - Medium - Low	l/s	592 - 422 - 342
	High - Medium - Low	m3/h	2130 - 1520 - 1230
Sound	Pressure High - Medium - Low	dB(A)	46 - 40 - 33
	Power High - Medium - Low	dB(A)	61 - 55 - 48
Unit	Height x Width x Depth	mm	319 x 840 x 840
	Weight	kg	25
Panel	Height x Width x Depth	mm	30 x 950 x 950
	Weight RBC-U32PGP-E	kg	4
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

### Accessories

<a href="#">RBC-AMTU31-E</a>	Standard Remote Controller - Full control including service functions
<a href="#">RBC-ASCU11-E</a>	Compact Remote Controller - Includes timer off, back light display, multilingual
<a href="#">RBC-AWSU52-E</a>	Premium Controller - Includes timer and back light display, multilingual (inc. Bluetooth)
<a href="#">RBC-MTSC1</a>	Mini Touch Screen Controller - with configurable icons for indoor units
<a href="#">RBC-MTSC2</a>	Mini Touch Screen Controller - with Schedule Timer, configurable icons for indoor units
<a href="#">TCB-GFC1603U-E</a>	Fresh Air Chamber - Fresh Air chamber for use with TCB-GB1602UE
<a href="#">TCB-BC1602UE</a>	Air discharge direction kit - Air Discharge kit - With 6-direction patterns
<a href="#">TCB-FF101URE2</a>	Auxiliary fresh air flange - For easy fresh air intake by using knock out hole of indoor.

\*All [Accessories](#) / [Controls](#)

Compatible R410a outdoor condensers:

[Mini SMMS-e](#), [SMMS-u](#), [SHRM-e](#)

Compatible R32 outdoor condensers:

[Mini SMMS](#), [SHRM-a](#)

Related items:

- [Full specification](#)
- [BIM files](#)
- [Airflow/ fan curve](#)
- [Dimensional drawing](#)
- [Wiring diagram](#)
- [Noise curve data](#)
- [Installation manual](#)

